

Specification								
Model Number	Type	Conductor Size	Insulation		Operating Temperature Range	Wire Grade	Color Code Japanese Standard JIS C1610-1989	
			Individual Insulation	Overall Jacket			Lead(+)Red	Lead(-)White
TC-CA-H	K	0.32X2	Glass	Glass	0-200°C	Thermocouple		
TC-IC-H	J		Fiber	Fiber				
TC-CA-H	K	0.65X2	Glass	Glass	0-200°C	Thermocouple		
TC-IC-H	J		Fiber	Fiber				
TC-CA-H(OS)	K	0.65X2	Glass	Tinned Copper	0-200°C	Thermocouple		
TC-IC-H(OS)	J		Fiber	Braided				
TC-CA-H(SOS)	K	0.65X2	Glass	SUS304	0-200°C	Thermocouple		
TC-IC-H(SOS)	J		Fiber	Stainless Braided				
TC-CA-H(SOS)	K	4/0.32X2	Glass	SUS304	0-200°C	Thermocouple		
TC-IC-H(SOS)	J		Fiber	Stainless Braided				
TC-CC-H(SOS)	T	0.65X2	Glass	SUS304	0-200°C	Thermocouple		
			Fiber	Stainless Braided				
WCA-H	K	4/0.32X2	Glass	Glass	0-200°C	Extension		
WIC-H	J		Fiber	Fiber				
WCA-H	K	7/0.32X2	Glass	Glass	0-200°C	Extension		
WIC-H	J		Fiber	Fiber				
WPR-H	R							
WCA-H	K	4/0.65X2	Glass	Glass	0-200°C	Extension		
WIC-H	J		Fiber	Fiber				
WPR-H	R							
WCA-H	K	7/0.65X2	Glass	Glass	0-200°C	Extension		
WIC-H	J		Fiber	Fiber				
WPR-H	R							
WCA-H(SOS)	K	7/0.32X2	Glass	SUS304	0-200°C	Extension		
WIC-H(SOS)	J		Fiber	Stainless Braided				
WCA-H(SOS)	K	4/0.65X2	Glass	SUS304	0-200°C	Extension		
WIC-H(SOS)	J		Fiber	Stainless Braided				
WPR-H(SOS)	R							
WCA-H(SOS)	K	7/0.65X2	Glass	SUS304	0-200°C	Extension		
WIC-H(SOS)	J		Fiber	Stainless Braided				
WPR-H(SOS)	R							
TC-CA-G	K	0.65X2	PVC	PVC	0-105°C	Thermocouple		
TC-CA-G	K	4/0.32X2	PVC	PVC	0-105°C	Thermocouple		
WCA-G	K	4/0.32X2	PVC	PVC	0-105°C	Extension		
WIC-G	J							
WCA-G	K	7/0.32X2	PVC	PVC	0-105°C	Extension		
WIC-G	J							
WCA-G	K	4/0.65X2	PVC	PVC	0-105°C	Extension		
WIC-G	J							
WCA-G	K	7/0.65X2	PVC	PVC	0-105°C	Extension		
WIC-G	J							
WCA-G(SOS)	K	7/0.32X2	PVC	SUS304	0-105°C	Extension		
WIC-G	J			Stainless Braided				
WCA-G(SOS)	K	7/0.65X2	PVC	SUS304	0-105°C	Extension		
WIC-G(SOS)	J			Stainless Braided				

Specification							
Model Number	Type	Conductor Size	Insulation		Operating Temperature Range	Wire Grade	Color Code Japanese Standard JIS C1610-1989
			Individual	Overall			
			Insulation	Jacket			
WCA-G-IS	K	7/0.32X2	PVC	PVC with Tinned Copper Braided Shield	0-105°C	Extension	
WCA-G-IS	K	4/0.65X2	PVC	PVC with Tinned Copper Braided Shield	0-105°C	Extension	
WIC-G-IS	J						
WPR-G-IS	R						
WCA-G-IS	K	7/0.65X2	PVC	PVC with Tinned Copper Braided Shield	0-105°C	Extension	
WIC-G-IS	J						
WCC-G	T	4/0.32X2	PVC	PVC	0-105°C	Extension	
WCC-G	T	7/0.32X2	PVC	PVC	0-105°C	Extension	
EX-G-IS	E	4/0.65X2	PVC	PVC	0-105°C	Extension	
TC-PH-H(SOS)	PT100	0.65X3	Glass Fiber	SUS304 Stainless Braided	0-200°C	RTD	
RTD-PVC	PT100	21/0.12X3	PVC	PVC	0-200°C	RTD	
RTD-Silicon	PT100	24AGW	Silicon	Silicon	0-200°C	RTD	
RTD-Teflon	PT100	24AGW O.D.: 2.6mm	Teflon	Teflon	0-200°C	RTD	
RTD-Teflon	PT100	24AGW O.D.: 3.0mm	Teflon	Teflon	0-200°C	RTD	
20-KK-GG	K	0.81X2	Glass Fiber	Glass Fiber	480°C~540°C	Thermocouple	
24-KK-GG	K	0.51X2	Glass Fiber	Glass Fiber	480°C~540°C	Thermocouple	
K-Type Teflon	K	1/0.32X2	Teflon	Teflon	0~200°C	Thermocouple	
J-Type Teflon	J						
T-Type Teflon	T					Thermocouple	
K-Type Teflon	K	1/0.65X2	Teflon	Teflon	0~200°C	Thermocouple	
K-Type Teflon	K	7/0.32X2	Teflon	Teflon	0~200°C	Thermocouple	
K-Type Teflon	K	19/0.12X2	Teflon	Teflon	0~200°C		